

Tehran, Tehransar

پتروفرهان گستر جنوب



LIGHT TRANSMITTER

Model : TR-LXT1A4

ISO-9001, CE, IEC1010



Lutron

LUTRON ELECTRONIC



The Art of Measurement

+982165565901

+982144584619

+989034119385

پتروفرهان گستر جنوب

FGJ-NDT.IR

DIGINDT.IR



LIGHT TRANSMITTER

Model : TR-LXT1A4

Measure Range	<p><i>Range 1 :</i> 0-2,000 Lux</p> <p><i>Range 2:</i> 2,000-20,000 Lux</p> <p><i>Range 3 :</i> 20,000-50,000 Lux</p>
Output	<p>4 - 20 mA</p> <p><i>Range 1 :</i> 0 Lux = 4 mA 1,000 Lux = 12mA 2,000 Lux = 20 mA</p> <p><i>Range 2:</i> 0 Lux = 4 mA 2,000 Lux = 5.6mA 20,000 Lux = 20mA</p> <p><i>Range 3 :</i> 0 Lux = 4 mA 20,000 Lux = 10.4 mA 50,000 Lux = 20 mA</p>
External Adjustment	ZERO VR SPAN VR
Power Supply	90 - 260 ACV 50 Hz/60 Hz
Operation Temperature	0 - 50 °C 32 - 122 °F
Operation Humidity	Less than 80 %RH
Accessory Included	Light probe
Mounting	Din rail or Wall Wall
Case	ABS plastic
Others	Separate probe with plug

* Appearance and specifications listed in this brochure are subject to change without notice.

+982165565901

+982144584619

+989034119385

پتروفرهان گستر جنوب

FGJ-NDT.IR

DIGINDT.IR