

پتروفهان گستر جنوب



پتروفهان گستر جنوب

FGJ-NDT.IR

DIGINDT.IR

+982165565901

+982144584619

+989034119385

Specifications

MS7221

Measurement and Output Voltage Parameter

Function	Range	Resolution	Accuracy
DC V mV Input	0~100mV	0.01mV	
	0~10V	0.001V	
DC V mV Output	0~100mV	0.01mV	
	0~10V	0.001V	
Loop Power Output	24V DC	N/A	
DC mA Input	0~24 mA	0.001mA	
DC mA Output	0~24 mA	0.001mA	
DC V Input and Output	100mV	0.01mV	±(0.02%+2)
	10V	0.001V	±(0.02%+2)
DC mA Input and Output	24mA	0.001mA	±(0.015%+4)
Loop Power	24V		±10%

Features

Storage Temperature	-40°C~60°C
Operating Temperature	-10°C~55°C
Operating Altitude	3000 meters maximum
Temperature Coefficient	±0.005% of range per °C for the TEMP range -10~18°C and 28~55°C
Relative Humidity	95% up to 30°C 75% up to 40°C 45% up to 50°C 35% up to 55°C
Shock	Random 2g 5Hz~500Hz
LBD	Low Battery Display

General

Power Supply	1×9V6F22 Battery
Product Size	190mm×90mm×43mm/7.67"×3.54"×1.7"
Product Weight	350g/0.77lb
Safety Rating	CE(EMC) RoHS