

## پتروفرهان گستر جنوب

Tehran, Tehransar



پتروفرهان گستر جنوب

FGJ-NDT.IR

DIGINDT.IR

+982165565901

+982144584619

+989034119385

## Specifications

MS2015A MS2015B

Specifications	Range	Accuracy	
DC Voltage	60mV/600mV/6V/60V/600V	±(0.7% +3)	
	600mV/6.6V/66V/660V		±(0.5% +3)
	1000V	±(0.8% +2)	±(0.8% +2)
AC Voltage	60mV/600mV/6V/60V/600V	±(0.8% +3)	
	600mV/6.6V/66V/660V		±(0.8% +3)
AC Current	750V	±(1% +4)	±(1% +4)
	60A/600A/1000A	±(2.0% +6)	
	66A/660A/1000A		±(2.0% +3)
Resistance	600Ω/6kΩ/60kΩ/600kΩ/6MΩ	±(0.8% +3)	
	60MΩ	±(1.2% +3)	
	660Ω/6.6kΩ/66kΩ/660kΩ/6.6MΩ		±(1.0% +3)
Capacitance	66MΩ		±(1.5% +3)
	10nF/100nF/1000nF/10μF/ 100μF/1000μF/10mF/100mF	±(4.0% +5)	
	6.6nF/66nF/660nF/6.6μF/ 66μF/660μF/6.6mF/66mF		±(4.0% +3)
Frequency (From Clamp)	0~10KHz	±(1.5% +5)	±(1.5% +5)
Frequency (AC Voltage)	0~10KHz	±(1.5% +5)	±(1.5% +5)
Logic Frequency	0~10MHz	±(0.5% +3)	
	0~66MHz		±(0.5% +3)
Duty Cycle	10%~90%	±3.0%	±3.0%
Temperature(°C)	-20°C~1000°C		±(2% +4)
Temperature(°F)	-4°F~1832°F		±(2% +4)
<b>Features</b>			
Display	counts	6000	6600
Jaw Opening		Φ40mm/1.6"	Φ40mm/1.6"
Auto Ranging		●	●
Manual Ranging		●	●
Auto Power Off		●	●
REL	Relative Measurement	●	●
Diode	2.7V	●	●
Continuity Buzzer	<50Ω	●	●
MAX/MIN		●	●
Data Hold		●	●
Display Backlight		●	●
Low Battery Display		●	●
Work Light		●	●
True RMS	True Root Mean Square Measurement	●	
NCV	Non-Contact Voltage Detector	●	●
<b>General</b>			
Power Supply	1×9V 6F22 Battery		
Product Size	238mm×92mm×50mm/9.37"×3.6"×1.9"		
Product Weight	390g/0.86lb		
Safety Rating	CE CAT.III 1000V RoHS		