

پتروفرهان گستر جنوب



پتروفرهان گستر جنوب

FGJ-NDT.IR

DIGINDT.IR

+982165565901

+982144584619

+989034119385

Specifications		MS2203	MS2205
Specifications	Range	Accuracy	
AC Voltage(V)	0.1V ~ 600V	±(1.2%+5)	±(1.0%+5)
AC Current(A)	0.01A ~ 1000A	±(2%+5)	±(2.0%+5)
Active Power(kW)	0.01kW ~ 600kW	±(3%+5)	±(3.0%+5)
Apparent Power(kVA)	0.001kVA ~ 600kVA	±(3%+5)	±(3.0%+5)
Reactive Power(kVAr)	0.001kVAr ~ 600kVAr	±(4%+5)	±(3.0%+5)
Power Factor	0.3 ~ 1	±(2%+2)	±(2.0%+2)
Active Energy(kWh)	0.001kWh ~ 10000kWh	±(3%+2)	
Frequency(Hz)	20Hz ~ 1000Hz	±0.5%	
Harmonic Measurement 45Hz~65Hz (fundamental frequency)	Harmonic Number :1		±(3.0%+10)
	Harmonic Number :2-6		±(3.5%+10)
	Harmonic Number :7-8		±(4.5%+10)
	Harmonic Number :9-10		±(5.0%+10)
	Harmonic Number :11-15		±(7.0%+10)
	Harmonic Number :16-20		±(10%+10)
Features			
Display	counts	9999	6000
Jaw Opening	Φ50mm/2.0"	●	●
Auto Ranging		●	●
Auto Power Off		●	●
Data Logging	groups	28	100
True RMS	True Root Mean Square Measurement	●	●
Dual Display		●	●
Segments Bar Graph		●	
MAX/MIN		●	
Data Hold		●	●
Display Backlight		●	●
RS232 Interface	Windows OS	●	●
General			
Power Supply	4x1.5V AA Batteries		
Product Size	300mmx103mmx51mm/11.8"x4.1"x2.0"		
Product Weight	640g/1.4lb		
Safety Rating	CE CAT III 600V RoHS		