

پتروفرهان گستر جنوب

Tehran, Tehransar



پتروفرهان گستر جنوب

FGJ-NDT.IR

DIGINDT.IR

+982165565901

+982144584619

+989034119385

Specifications

MS8050

Specifications	Range	Accuracy
DC Voltage	50mV/500mV/5V/50V/500V/1000V	±(0.03% +6)
AC Voltage	50mV/500mV/5V/50V/500V/1000V	±(0.5% +40)
DC Current	500μA/5mA/50mA/500mA 5A/10A	±(0.15% +10) ±(0.5% +10)
AC Current	500μA/5mA/50mA/500mA 5A/10A	±(0.75% +10) ±(1.0% +10)
Resistance	500Ω/5KΩ/50KΩ/500KΩ/5MΩ 50 MΩ	±(0.1% +5) ±(0.5% +10)
Capacitance	50nF/500nF/5μF/50μF 500μF/5000μF	±(1% +10) ±(2% +10)
Logic Frequency	5Hz ~2MHz	±(0.006% +4)
Duty Cycle	10%~90%	±1.0%
Linear Frequency	5Hz~200kHz	±(0.006% +4)

Features

Display	53000 counts
Auto Ranging	●
Manual Ranging	●
Voltage & Current AC+DC Measurement	mV, V, μA, mA, A
True RMS	For AC Voltage & AC Current
dBm Measurement	4Ω, 8Ω, 16Ω, 32Ω, 50Ω, 75Ω, 93Ω, 110Ω, 125Ω, 135Ω, 150Ω, 200Ω, 250Ω, 300Ω, 500Ω, 600Ω, 800Ω, 900Ω, 1000Ω, 1200Ω
Relative Measurement	●
Diode	2.5V
Continuity Buzzer	<50Ω
MAX/MIN/MAX-MIN/AVG	●
Data Hold	●
Data Logging	30 groups
VFD Display	●
USB Interface	Windows OS
General	
Power Supply	220V/110V AC
Product Size	320mm×255mm×106mm / 12.6"×10"×4.17"
Product Weight	3112g/6.85lb
Safety Rating	CE CAT.II 1000V RoHS