

پترو فرهان گستر جنوب

Tehran, Tehransar

Specifications		MS8216
Specifications	Range	Accuracy
DC Voltage	400mV/4V/40V/400V/600V	$\pm(0.7\%+2)$
AC Voltage	4V/40V/400V/600V	$\pm(0.8\%+3)$
Resistance	400 Ω /4K Ω /40K Ω /400K Ω /4M Ω	$\pm(1.2\%+2)$
	40M Ω	$\pm(2.0\%+5)$
Capacitance	4nF/40nF/400nF/4 μ F/40 μ F/200 μ F	$\pm(3.0\%+3)$
Frequency	9.999Hz	$\pm(2.0\%+5)$
	99.99Hz/999.9Hz/9.999kHz	$\pm(1.5\%+5)$
	99.99kHz/199.99kHz	$\pm(2.0\%+5)$
	>200kHz	Take it only as reference
Duty Cycle	0.1%~99.9%	$\pm 3.0\%$
Features		
Display	counts	4000
Auto Ranging	Auto & manual	●
APO	Auto Power Off	●
REL	Relative Measurement	●
Diode	2.7V	●
Continuity Buzzer	<40 Ω	●
LBD	Low Battery Display	●
Data Hold		●
General		
Power Supply	357A(LR44) Battery/1.5V×2 Batteries	
Product Size	110mm×76mm×11mm/4.3"×3.07"×0.47"	
Product Weight	85g/0.19lb	
Safety Rating	ETL CAT II 600V RoHS	



+982165565901

+982144584619

+989034119385

پتروفرهان گستر جنوب

FGJ-NDT.IR

DIGINDT.IR