

## پتروفرهان گستر جنوب

Tehran, Tehransar



پتروفرهان گستر جنوب

FGJ-NDT.IR

DIGINDT.IR

+982165565901

+982144584619

+989034119385

Specifications	Range	Accuracy		
DC Voltage	400mV			$\pm(0.8\%+3)$
	4V/40V/400V			$\pm(0.5\%+5)$
	1000V			$\pm(0.8\%+3)$
	660mV	$\pm(0.8\%+3)$	$\pm(0.8\%+3)$	
	6.6V/66V	$\pm(0.5\%+5)$	$\pm(0.5\%+5)$	
	1000V	$\pm(0.8\%+3)$	$\pm(0.8\%+3)$	
AC Voltage	400mV(40~60Hz)			$\pm(1.5\%+5)$
	4V/40V/400V(40~400Hz)			$\pm(1.2\%+5)$
	1000V(40~400Hz)			$\pm(1.0\%+3)$
	660mV(40~60Hz)	$\pm(1.5\%+5)$	$\pm(1.5\%+5)$	
	6.6V/66V(40~400Hz)	$\pm(1.2\%+5)$	$\pm(1.2\%+5)$	
	1000V(40~400Hz)	$\pm(1.0\%+3)$	$\pm(1.0\%+3)$	
DC Current	400/4000 $\mu$ A/40/400mA			$\pm(1.0\%+5)$
	660/6600 $\mu$ A/66/660mA	$\pm(0.8\%+2)$	$\pm(0.8\%+2)$	
	10A	$\pm(2.0\%+5)$	$\pm(2.0\%+5)$	$\pm(2.0\%+5)$
AC Current	400/4000 $\mu$ A/40/400mA			$\pm(1.5\%+5)$
	660/6600 $\mu$ A/66/660mA	$\pm(1.5\%+5)$	$\pm(1.5\%+5)$	
	10A	$\pm(3.0\%+5)$	$\pm(3.0\%+5)$	$\pm(3.0\%+5)$
Resistance	400 $\Omega$ /4/40/400k $\Omega$ /4M $\Omega$			$\pm(0.8\%+5)$
	40M $\Omega$			$\pm(1.5\%+5)$
	660 $\Omega$ /6.6/66/660k $\Omega$ /6.6M $\Omega$	$\pm(0.8\%+5)$	$\pm(0.8\%+5)$	
	66M $\Omega$	$\pm(1.5\%+5)$	$\pm(1.5\%+5)$	
Capacitance	4nF			$\pm(4.0\%+5)$
	40/400nF/4/40/400 $\mu$ F			$\pm(3.0\%+3)$
	4mF/40mF			$\pm(4.0\%+5)$
	6.6nF	$\pm(4.0\%+5)$		
	66/660nF/6.6/66/660 $\mu$ F	$\pm(3.0\%+3)$		
Frequency (V position)	40/400Hz/4/10kHz			$\pm(1.5\%+5)$
	66/660Hz/6.6/10kHz	$\pm(1.5\%+5)$	$\pm(1.5\%+5)$	
Frequency (Hz position)	40/400Hz/4/40/400kHz/4/40MHz			$\pm(1.5\%+5)$
	66/660Hz/6.6/66/660kHz/6.6/66MHz	$\pm(1.5\%+5)$	$\pm(1.5\%+5)$	
Duty Cycle	1%~99%	$\pm(2.0\%+2)$	$\pm(2.0\%+2)$	$\pm(2.0\%+2)$
Temperature	0~1000°C/32~1832°F	$\pm(2.0\%)$	$\pm(2.0\%)$	$\pm(1.0\%+3)$