

پتروفرهان گستر جنوب

Tehran, Tehransar



پتروفرهان گستر جنوب

FGJ-NDT.IR

DIGINDT.IR

+982165565901

+982144584619

+989034119385

Specifications	Range	Accuracy	
DC Voltage	600mV	±(0.5%+3)	
	6V/60V/600V/1000V	±(0.8%+3)	
	220mV		±(0.05%+3)
AC Voltage	2.2V/22V/220V/1000V		±(0.1%+3)
	6V/60V/750V(50Hz)	±(1.0%+4)	
	6V/60V/750V(2kHz)	±(2.0%+3)	
	220mV/2.2V/22V/220V/700V(50Hz)		±(0.8%+4)
DC Current	220mV/2.2V/22V/220V/700V(2kHz)		±(2.5%+3)
	600uA/6mA/60mA/600mA/10A	±(1.2%+4)	
	220uA/2200uA/22mA/220mA/10A		±(1.0%+4)
AC Current	600uA/6mA/60mA/600mA	±(1.5%+3)	
	10A	±(2.0%+3)	
	220uA/2200uA/22mA		±(1.5%+3)
Resistance	220mA/10A		±(1.8%+3)
	600Ω/6KΩ/60KΩ/600KΩ/6MΩ/60MΩ	±(1%+2)	
	220Ω/2.2KΩ/22KΩ/220KΩ		±(0.8%+2)
Capacitance	2.2MΩ/22MΩ/220MΩ		±(1.0%+2)
	40nF/400nF	±(3.0%+2)	
	40n4uF/40uF/400uF		±(3.5%+2)
Frequency	22nF/220nF/2.2uF/22uF/220uF/2.2mF/22mF/220mF		±(2.5%+3)
	0~10MHz	±(0.2%+3)	
	0~220MHz		±(0.2%+3)
Duty Cycle	5%~95%	±1%	±1%
Temperature	-10°C~700°C	±(2%+2)	
	14°F~1292°F	±(2%+4)	
Special Functions			
LCD Display	counts	6000	22000
Auto Ranging	Auto & manual	●	●
APD	Auto Power Off	●	●
REL	Relative Measurement	●	●
PEAK	Peak Measurement	●	●
LPF	1KHz Low Pass Filter	●	
Diode	2.7V	●	●
Continuity Buzzer	<50Ω	●	●
MAX/MIN		●	●
Data Hold		●	●
True RMS		●	●
Display Backlight		●	●
LBD	Low Battery Display	●	●
USB Interface	Windows OS		●
General			
Power Supply	4×1.5V AA Batteries		
Product Size	205mm×102mm×58mm/8.1"×4.0"×2.2"		
Product Weight	390g/0.86lb		
Safety Rating	CE GS CAT. III 1000V		