



Specifications	Range	Resolution	Accuracy
DC Voltage	6V/60V/600V	0.01V/0.1V/1V	±(0.5%+3)
AC Voltage	6V/60V/600V	0.01V/0.1V/1V	±(0.8%+5)
AC Current	2A/20A/200A	0.01A/0.01A/0.1A	±(2.5%+8)
	600A	1A	±(3.0%+10)
Resistance	2kΩ/20kΩ/200kΩ/2MΩ	0.001kΩ/0.01kΩ/0.1kΩ/0.001MΩ	±(0.8%+3)
	10MΩ	0.01MΩ	±(1.0%+5)
Frequency (Clamp)	60Hz/600Hz/3kHz	0.1Hz/1Hz/10Hz	±(1.0%+5)
Frequency (Plug)	60Hz/600Hz/3kHz	0.1Hz/1Hz/10Hz	±(1.0%+5)
Duty Cycle	10% ~ 90%	1%	±2.0%
Features			
Display	counts		6000
Jaw Opening			Ø26mm/1.0"
Auto range	Auto		•
APO	Auto Power Off		•
Dual Display			•
Continuity Buzzer	<40Ω		•
A Hold	Data Auto hold		•
MAX/MIN			•
Display Backlight			•
LBD	Low Battery Display		•
General			
Power Supply	3×1.5V AAA Batteries		
Product Size	204mm×78mm×43mm/8"×3.07"×1.77"		
Product Weight	195g/0.43lb		
Certificate	CE/ETL/RoHS		
Safety Rating	CAT III 600V		

+982165565901

+982144584619

+989034119385

پتروفرهان گستر جنوب

FGJ-NDT.IR

DIGINDT.IR