



Specifications	Testing Voltage	Range	Resolution	Accuracy
Resistance	0.5V RMS	60Ω	0.01Ω	±(2.0%+10)
		600kΩ/6kΩΩ/ 60kΩ/600kΩ	0.1Ω/0.001kΩ/ 0.01kΩ/0.1kΩ	±(1.0%+5)
		6MΩ/20MΩ	0.001MΩ/0.01MΩ	±(2.0%+5)
	0.1V RMS	60Ω	0.01Ω	±(2.0%+10)
		600kΩ/6kΩΩ/ 60kΩ/600kΩ	0.1Ω/0.001kΩ/ 0.01kΩ/0.1kΩ	±(1.5%+5)
		6MΩ/20MΩ	0.001MΩ/0.01MΩ	±(3.0%+5)
Capacitance	0.5V RMS	600pF	0.1pF	±(2.0%+8)
		6nF/60nF/600nF	0.001nF/0.01nF/0.1nF	±(1.0%+5)
		6μF/60μF	0.001μF/0.01μF	±(2.0%+5)
	0.1V RMS	600μF	0.1μF	±(2.0%+10)
		6mF	0.001mF	±(2.0%+5)
		600pF	0.1pF	±(2.0%+5)
Inductance	0.5V RMS	6nF/60nF/ 600nF/6μF	0.001nF/0.01nF/ 0.1nF/0.001μF	±(1.5%+5)
		60μF/600μF/6mF	0.01μF/0.1μF/0.001mF	±(3.0%+5)
		600μH/6000μH	0.1μH/1μH	±(2.0%+5)
	0.1V RMS	60mH/600mH/ 6H/60H	0.01mH/0.1mH/ 0.001H/0.01H	±(1.0%+5)
		200H	0.1H	±(2.0%+5)
		600μH/6000μH	0.1μH/1μH	±(3.0%+5)
0.1V RMS	60mH/600mH/6H	0.01mH/0.1mH/0.001H	±(1.5%+5)	
	60H	0.01H	±(1.0%+5)	
	200H	0.1H	±(2.0%+5)	
Features				
Display	counts			6000
Auto Ranging	Auto & Manual			•
APO	Auto Power Off			•
Data Hold				•
LBD	Low Battery Display			•
Auto Scanning				•
General				
Power Supply	1×3V CR2450 Battery			
Product Size	186mm×35mm×23.6mm/7.3"×1.38"×0.93"			
Product Weight	90g/0.2lb			
Certification	CE /ETL/RoHS			