

پتروفرهان گستر جنوب

Tehran, Tehransar



Test Force	3 ~ 250kgf
Brinell Scale	HBW1/5, HBW2.5/62.5, HBW1/10, HBW2.5/15.625, HBW1/30, HBW2.5/31.25, HBW2.5/62.5, HBW10/100, HBW5/125, HBW2.5/187.5, HBW5/250, HBW10/250 (select 10 scales)
Rockwell Scales	HRA, HRB, HRC, HRD, HRE, HRF, HRG, HRH, HRK, HRL, HRM, HRP, HRR, HRS, HRV
Superficial Rockwell Scales	HR15N, HR15T, HR15W, HR15X, HR15Y, HR30N, HR30T, HR30W, HR30X, HR30Y, HR45N, HR45T, HR45W, HR45X, HR45Y
Vickers Scales	HV3, HV5, HV10, HV20, HV30, HV40, HV50, HV60, HV80, HV100, HV120 (select 10 scales)
Hardness resolution	0.1HB, 0.1HR or 0.1HV
Objective	2.5X, 5X (10X, 20X optional)
Magnification of microscope	Brinell: 37.5X, Vickers: 75X
Hardness measuring range	For Brinell: 8 ~ 650 HBW For Rockwell: 20~95 HRA, 10~100HRBW, 20-70 HRC For Vickers: 8 ~ 2900 HV
Maximum specimen height	220mm for Rockwell testing, 170mm for Brinell and Vickers hardness testing (Customization Rockwell: 350mm, Brinell & Vickers: 280mm)
Depth of throat	200mm
Data output	Touchable LCD display, USB Flash Disk
Dwelling Time	1 ~ 99s
Power supply	AC 220V or 110V, 50 or 60Hz, single phase
Dimensions	560mm×260mm×800 mm
Weight	70 Kg

پتروفرهان گستر جنوب

FGJ-NDT.IR

DIGINDT.IR

+982165565901

+982144584619

+989034119385